



For technical reasons connected with colour reproduction in printing, the actual shades may vary.



DARK BROWN

Also available in Black & White.



JOINT FILLING CEMENT POLYMER GROUT

 $\label{lem:component} \mbox{ACROTILE } \mbox{\bf G} \mbox{ is a single component joint filling compound based on cement, polymer and specialty chemicals}$ **DESCRIPTION**

USES

ACROTILE G can be used for joint grouting of ceramic, mosaic, marble, granite, resin bonded marble, natural stones, terrazzo tiles and swimming pool tiling.

METHOD OF USE • Mix 3 parts of Powder with 1 parts of water to a smooth blend of creamy consistency and leave for 5-10 minutes. •Remix the composite. •Apply mixed paste by means of a spatula/trowel. •Clean the excess material by means of a

soft sponge/cloth and water after about 10-15 minutes of applications. ADVANTAGES

•Pre-measured quantity ensures total quality. •Highly resistant to water permeability. •Crack resistant due to flexible in nature.•Excellent adhesive strength. •Longer workable time. •UV resistance. •Most properties improve with age. •Non-staining.

DIRECTIONS FOR USE Add 1 part of water to 3 parts of grout by weight and mix well to obtain a smooth and uniform paste. Use the mixed material with in 20 minutes of mixing.

Apply the paste by means of a spatula/trowel into the tile joints. Use the mixed material within 20 minutes of mixing.

Clean the excess material by means of a soft sponge/cloth and water after about 10-15 minutes of application.

PRECAUTION Filling of joints should be done 24 hours after fixing of



and Waterproofing Products from the house of

a acro paints

TERRACOTTA



ACRO PAINTS LIMITED

'Acro House' 5/3, Kirti Nagar Industrial Area, New Delhi -110015 Ph.: 011-43340000 (100 Lines), Toll Free: 1800-11-8880 Fax: 011-25419683, 25410464, E-mail: acro@del2.vsnl.net.in Website: www.acropaints.net, www.spanezia.com CIN No.: U24119DL1989PLC036308

