



Acro Wudsaver

Specialised Wood Preservative



ACRO WUDSAVER is a specialized colorless to light brown wood preservative. It is highly effective against termites and increases the life of wood. Acro Wudsaver is a specialized wood preservative is ready to use and easy to apply solution. It is eco-friendly and non-toxic therefore it is safe to use but you should wear gloves during application. Acro Wudsaver does not leave any strong smell.

PRODUCT BENEFITS



PRODUCT FEATURES

AREAS OF APPLICATION



Interior Wood Surfaces



Doors



Cabinets



Furniture

PACKAGING AVAILABLE

500 ml.

1 Ltr.

Shelf Life: 3 years from date of manufacturing in original tightly closed containers away from direct sunlight and excess heat.

FINISH

NA*

COVERAGE

On smooth sanded wooden surface



1 COAT
15 sq. mtr./ltr.*

*Actual coverage may vary from the quoted coverage due to factors such as method and conditions of application, surface roughness and porosity.

COLOURS AVAILABLE

NA*

*Acro Wudsaver is an clear top coat

HOW TO APPLY

APPLICATION

- Remove grease, dust particles from the surface.
- Apply one coat of Acro Wudsaver specialized wood preservative to the surface with brush spray or by injection.
- On highly effected area it can be applied 2coats to get desired effect.
- Do not dilute with any other product as it may reduce its effect.
- Brush, spray and injection can be used.

PAINT APPLICATION PROCESS

APPLICATION	THINNER	DILUTION % (BY VOLUME)	APPLICATION VISCOSITY(SEC)	RECOATING PERIOD (HOURS)
STEP 1 FIRST COAT ACRO WUDSAVER SPRAY/BRUSH/INJECT	NA	NA	SPRAY 12 - 13 BRUSH 12 - 13 INJECT 12 - 13	2 HRS
STEP 2 SECOND COAT ACRO WUDSAVER SPRAY/BRUSH/INJECT	NA	NA	SPRAY 12 - 13 BRUSH 12 - 13 INJECT 12 - 13	2 HRS

DO NOT SAND THE ACRO WUDSAVER COAT

1. As measured through a Ford cup.

2. Recoating period is quoted for 30°C and 75% relative humidity, these may vary under different conditions.

TECHNICAL DETAILS

a. Drying time: Surface dry time 30 min

b. Flash point IS101/1987 Part 1, Sec 6: Above 60°C (140°F)

c. Stability of thinned paint: NA

PRECAUTIONS

- ❖ For optimum performance, Acro Wudsaver must be applied at a temperature between 20°C and 40°C and humidity not above 75%.
- ❖ Stir well.

SAFETY FEATURES

- ❖ Kindly refer to the MSDS for Acro Wudsaver which gives detailed information on safety measures while handling the paint.
- ❖ Store the product at ambient conditions in well ventilated locations and away from source of ignition and fire.
- ❖ Use protective equipment like rubber/polyurethane gloves, safety goggles/glasses, face mask while handling the paint.
- ❖ Avoid eye and skin contact. In both cases wash with soap and plenty of water. Get medical attention if irritation develops or persists.
- ❖ Do not inhale or ingest. In case of inhalation move to fresh air and seek medical attention if symptoms persist in both cases.
- ❖ Do not dispose in any drain or land filling.
- ❖ No added lead, mercury or chromium compounds.
- ❖ Flammable liquid.