


Acro Wudstain




Acro Wudstain is a solvent based finish, it offers excellent transparent shades, uniform finish and good durability.

PRODUCT BENEFITS



PRODUCT FEATURES

AREAS OF APPLICATION



Interior Wood Surfaces



Doors



Cabinets



Furniture

PACKAGING AVAILABLE



Shelf Life: 3 years from date of manufacturing in original tightly closed containers away from direct sunlight and excess heat.

FINISH

SMOOTH ✓

GLOSSY ✓

COVERAGE

On normal masonry surface by Spray



1 COAT

60 - 70 sq. ft. / ltr.*

*Actual coverage may vary from the quoted coverage due to factors such as method and conditions of application, surface roughness.)

COLOURS AVAILABLE

Teak, Charcoal, Walnut, Red Brown, Red, Green, Wenge, Oak Yellow, Rose Wood

HOW TO APPLY

SURFACE PREPARATION:



Sand the wooden surface along the grains using sand paper no. 180, and then 320 or 400. Wipe surface to clean off loose dust particles.

APPLICATION

- Apply Acro Wudstain with muslin cloth pad smoothly along with grains. Apply additional coats, with an intercoat interval of 5-10 min till desired shade is obtained.

- For lighter tone dilute the stain with adding good quality NC thinner and then apply.
- Allow to dry for 30 min before apply sealer coat.

PAINT APPLICATION PROCESS

APPLICATION	THINNER	DILUTION % (BY VOLUME)	APPLICATION VISCOSITY(SEC)	RECOATING PERIOD (HOURS)
STEP 1 FIRST COAT ACRO WUDSTAIN SPRAY/BRUSH	 MTO	SPRAY 20 - 25 BRUSH 0 - 5	SPRAY 20 - 25 BRUSH 30 - 55	24 HRS
SAND THE FILLED SURFACE WITH EMERY PAPER 320 / 400				
STEP 2 SECOND COAT ACRO WUDSTAIN SPRAY/BRUSH	 MTO	SPRAY 20 - 25 BRUSH 0 - 5	SPRAY 20 - 25 BRUSH 30 - 55	24 HRS
APPLY THIRD COAT IF REQUIRED AFTER SANDING WITH EMERY PAPER NO. 320 / 400				

POST PAINTING CARE

For the best performance of the paint, ensure proper washing and cleaning of all algal and fungal growth, if any, at regular intervals of six months.

TECHNICAL DETAILS

a. Drying time: Surface dry time 15 min

b. Sheen levels: 3 - 12 at 60 deg GH

c. Flash point IS101/1987 Part 1, Sec 6: NA

d. Stability of thinned paint: To be used within 24 hours

PRECAUTIONS

- ❖ For optimum performance, Acro Wudstains must be applied at a temperature between 20°C and 40°C and humidity not above 75%
- ❖ Do not over-thin and mix according to recommended ratios stir well and strain before use.

SAFETY FEATURES

- ❖ Kindly refer to the MSDS for Acro Wudstain which gives detailed information on safety measures while handling the paint.
- ❖ Store the product at ambient conditions in well ventilated locations and away from source of ignition and fire.
- ❖ Use protective equipment like rubber/polyurethane gloves, safety goggles/glasses, face mask while handling the paint.
- ❖ Avoid eye and skin contact. In both cases wash with soap and plenty of water. Get medical attention if irritation develops or persists.
- ❖ Do not inhale or ingest. In case of inhalation move to fresh air and seek medical attention if symptoms persist in both cases.
- ❖ Do not dispose in any drain or land filling.
- ❖ No added lead, mercury or chromium compounds.
- ❖ Flammable liquid.