

Rhino

Acrylic Wall Putty

 **acro paints**




RHINO ACRYLIC WALL PUTTY for interiors is a thin coat surfacing putty to provide silky smooth finish. It has good sanding properties and is most ideal to remove interior surface imperfections. Being acrylic based, it gives excellent finishing & superior bonding with wall & top coat.

PRODUCT BENEFITS



PRODUCT FEATURES

AREAS OF APPLICATION




Interior Walls



Concrete



Cement Plaster



Concrete Bricks



Mortar Plaster

PACKAGING AVAILABLE



Shelf Life: 3 years from date of manufacturing in original tightly closed container away from direct sunlight and excess heat.

FINISH

SMOOTH 

MATT 

COVERAGE



1ST COAT

35 - 40 sq. ft. / kg.*



2ND COAT

25 - 30 sq. ft. / kg.*

*Actual coverage may vary from the quoted coverage due to factors such as method and conditions of application, surface roughness and porosity.

COLOURS AVAILABLE

White*

*Rhino Acrylic Wall Putty is an undercoat



HOW TO APPLY

SURFACE PREPARATION: The surface should be cleaned of dirt, dust, grease etc. Prepare the surface by sanding with emery paper 180 Wipe clean.

APPLICATION: Apply a first coat of cement primer (water or solvent thinnable) and allow it to dry for 6-8 hours. Smoothen the surface by filling dents with number of thin coats of Rhino Acrylic Wall Putty. Allow

it to dry for 4-6 hours, Sand it with emery paper 320 and Wipe clean. Follow this up with another coat of cement primer (water / solvent thinnable) and then apply the finish paint. The container should be properly closed when not in use to prevent drying of the material.

PAINT APPLICATION PROCESS

APPLICATION	THINNER	DILUTION % (BY VOLUME)	APPLICATION ¹ VISCOSITY(SEC)	RECOATING PERIOD ² (HOURS)
STEP 1 SANDING				
SAND LIGHTLY WITH SAND PAPER 180 AND WIPE CLEAN				
STEP 2 FIRST COAT RHINO ACRYLIC WALL PUTTY PUTTY KNIFE	 WATER IF REQUIRED	–	PASTE	4 - 6 Hrs.
STEP 3 SECOND COAT RHINO ACRYLIC WALL PUTTY PUTTY KNIFE	 WATER IF REQUIRED	–	PASTE	4 - 6 Hrs.

1. As measured through a Ford cup.

2. Recoating period is quoted for 25°C and 50% Relative Humidity, these may vary under different conditions.

TECHNICAL DETAILS

a. Drying time : Surface dry time 30 min.

b. Flash point IS101/1987 Part 1, Sec 6: NA

c. Stability of thinned paint: To be used within 24 hours

PRECAUTIONS

- ❖ Do not apply in temperature over 40°C or below 5°C and on damp surfaces.
- ❖ Freshly applied material should be protected from rain for minimum 48 hours.
- ❖ Prevent human traffic on the painted surface.

SAFETY FEATURES

- ❖ Kindly refer to the MSDS for RHINO ACRYLIC WALL PUTTY which gives detailed information on safety measures while handling the paint.
- ❖ Store the container with the lid tightly closed in an upright position, in a cool, dry place.
- ❖ Keep out of reach of children and away from food, drink etc.
- ❖ May be harmful, if swallowed. In case of ingestion, seek immediate medical attention.
- ❖ Wear eye protection during application. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- ❖ In case of skin contact immediately wash skin with soap and plenty of water. Get medical attention if irritation develops or persists.
- ❖ Do not breathe vapour or spray. It is recommended to wear suitable nose pad during sanding and surface preparation to avoid dust inhalation.
- ❖ Do not pour leftover paint down the drain or in water courses.
- ❖ In the event of spills, contain spillage using sand or earth.
- ❖ Safety Data Sheet available for professional user on request.
- ❖ No added Lead, Mercury or Chromium compounds.